

ELISA™

Valenteena™ Shower Heads



Installation and Care Guide

IMPORTANT INFORMATION

Introduction

The Valenteena™ range of shower heads has been designed for use with the Valenteena™ shower valves. Please select from the following options:

Option 1. Adjustable height head. Choose from adjustable height head concealed or exposed (compatible with any water system).

Option 2. 5" drencher head. Choose from exposed or concealed (compatible with most water systems – if fitting with a combination boiler, the appliance must have a minimum domestic hot water rating of 24kW (80,000 BTu) and be of the type fitted with a modulating gas valve. If in any doubt, please contact the appliance manufacturer before installation commences).

Option 3. 8" drencher head. Choose from exposed or concealed (compatible with high pressure or boosted systems only).

The installation of this shower head with anything other than an Eliscr™ shower valve may result in poor shower performance.

If you have any questions regarding the specification of compatible shower heads or at any stage during installation then please contact the Valenteena™ customer helpline on 01959 560003 for advice.

Safety information

This product must be installed by a competent person in accordance with all relevant current Water Supply Regulations.

Flushing

Some modern fluxes can be extremely corrosive and, if left in contact,

will attack the working parts of this unit. All soldering must be completed and the pipe work thoroughly flushed out in accordance with current Water Supply Regulations prior to connection of the product.

Connections

The Valenteena™ shower head range is suitable for use with 15mm British Standard copper tube. Tube should be cut using a rotary type cutter and lubricated using a silicone-based lubricant or petroleum jelly (Vaseline or similar) prior to insertion of the fitting. Supply lines must be flushed clear of any debris before installation of this unit.

This guide is to be used in conjunction with the valve fitting instructions (supplied separately). Please refer to the Valenteena™ Shower Valve installation guide.

We have taken great care to ensure that this product reaches you in perfect condition. However should any parts be damaged or missing please contact your point of purchase. This does not affect your statutory rights. In addition if you require replacement parts please contact the Valenteena™ customer helpline on 01959 560003 for assistance.

Valenteena™ products are supplied complete with a 1 year guarantee that can be upgraded by registering this product with Elisa™.

See www.elisabathrooms.com/guarantee



In addition to the guide below it is essential that the written instructions overleaf are read and understood and that you have all the necessary components (as shown) before commencing installation. Failure to install the product in accordance with these instructions may adversely affect the warranty terms and conditions. Do not undertake any part of this installation unless you are competent to do so. Prior to starting ensure that you are familiar with the necessary plumbing regulations required to install the product correctly and safely.

ADJUSTABLE HEIGHT HEAD INSTALLATION



The adjustable height heads are available to be fitted with either concealed or exposed shower valves. A wall outlet assembly is supplied with the concealed version shower head for installation with a concealed valve whereas the exposed version is supplied with 1/2" connector to replace the 3/4" connector fitted to the exposed valve as standard.

EXPOSED VALVE INSTALLATION



If fitting an exposed valve and suitable adjustable height head, it will be necessary to reverse the valve outlet and outlet plug and replace the 3/4" valve outlet with the 1/2" outlet connector supplied complete with the shower head.

1

Unscrew and remove the 3/4" outlet connector positioned at the top of the valve using a 12mm hexagonal key or radiator key.

2

Remove the outlet plug from the bottom of the valve using a snug fitting screwdriver taking care to avoid any damage to the plated surfaces. Refit in the top of the valve.

3

Fit the 1/2" connector supplied with shower kit into the bottom of the shower valve using a 12mm hexagonal key or radiator valve key taking care not to overtighten.

CONCEALED VALVE INSTALLATION



The concealed shower valve is supplied with the 3/4" BSP outlet positioned at the top of the valve and a blanking plug at the bottom. The outlet and plug can be reversed if required. The wall outlet is supplied with a 3/4" BSP male threaded connection 48mm long.

1

Run a 22mm outlet pipe from the shower valve to the preferred position for the wall outlet assembly. The pipe must terminate with a suitable 3/4" BSP female fitting.

2

If the shower system is being built into a solid wall, secure the pipe work to the rear of the chase using suitable fixings. Fill in the chase using suitable non-setting infill material. If the shower installation is of a panel mounted type, secure the wall outlet assembly to the panel using the nut and washer provided.



ADJUSTABLE HEIGHT HEAD INSTALLATION

1

Loosen the handset holder knob and pass the rail through the handset holder ensuring the holder is on the left.



2

Put the rail ends onto the rail and place the assembly in the desired location on the wall and mark the two fixing positions in each rail end. One end of the rail features a cut out which locates into the relevant rail end locking the rail in position ensuring it cannot rotate.

3

Drill and plug the four holes using the fixings provided, and secure the rail assembly to the wall.



4

Connect the shower handset to the conical end of the hose, ensuring the hose washer is fitted and place in the handset holder.

THE FRICTION OF THE HANDSET HOLDER IS FACTORY SET AND SHOULD NOT BE ADJUSTED.



5

Connect the other end of the hose to the valve outlet or to the wall outlet ensuring the hose washer is in position.



DRENCHER HEAD CONCEALED

1

Run a 22mm outlet pipe from the shower valve to the preferred position for the fixed arm assembly. The pipe must terminate with a suitable 3/4" BSP female fitting.

2

If the shower system is being built into a solid wall, secure the pipe work to the rear of the chase using suitable fixings. Fill in the chase using suitable non-setting infill material. If the shower installation is of a panel mounted type, secure the fixed wall assembly to the panel using the nut and washer provided.



If the assembly is to be fixed prior to tiling, the depth of the tiles must be taken into consideration.

3

Screw the shower arm cover plate flush to the finished wall surface and seal using a thin bead of silicone if necessary. Proceed to step 8 in the next section.



DRENCHER HEAD EXPOSED

1

Screw the formed shower arm to the riser tube. The riser tube can be shortened if required by trimming the plain end using a rotary type cutter.



2

Carefully slide the fixing bracket up the riser tube until the joint is hidden.



3

Locate the riser tube into the 3/4" valve outlet and place in the required position against the wall face.

4

Mark the required fixings holes and remove the riser tube assembly from the valve. Drill and plug the holes using the fixings provided, ensuring no debris enters the shower valve.

5

Carefully slide the plated 3/4" nut and 'O' ring onto the riser tube and locate the assembly into the 3/4" valve outlet. Fix the wall stay to the wall using the screws provided, if suitable.



6

Carefully tighten the 3/4" nut using either 31mm A/F spanner or a tool with smooth jaws just sufficiently to compress the 'O' ring and achieve a watertight seal.

7

Tighten the locking screw in the side of the wall stay using the hexagonal key provided.



8

Screw the drencher head to the shower head arm taking care not to damage the plated surfaces. Carefully tighten the shower head with a suitable spanner or a tool with smooth jaws just sufficiently to lock the head in position.



AFTER INSTALLATION

Run through the valve operation with the purchaser and hand them this guide. Complete and post the Valenteena™ shower head guarantee card or register online at www.elisabathrooms.com/guarantee

Adjustable height shower user guide

To select the preferred height for the shower head, turn the knob on the side of the handset holder to enable the slider to be moved up or down the rail. Tighten the knob when the holder is in the desired position



Drencher head user guide

The angle of the drencher shower heads can be adjusted. The shower head is mounted on a multi directional ball joint to allow for angular adjustment in any direction by carefully moving the head to the desired angle.



Cleaning

Whilst modern plating techniques are used in the manufacture of these fittings, the plating will wear if not cleaned properly. The safest way to clean your product is to wipe with a soft damp cloth. Stains can be removed using washing up liquid.



DO NOT USE ABRASIVE CLEANERS. Should chemical descaling of the head become necessary, remove the shower head and fully immerse in a mild proprietary descalent.



It is imperative that descaling is carried out strictly in accordance with the manufacturer's instructions. Substances that are not suitable for plastics and electroplated surfaces must not be used.

COMPONENTS

Valenteena™ adjustable height shower kit concealed
Chrome VTN.FLX.EXP.CP
Gold Plated VTN.FLX.EXP.GD



Valenteena™ 8" drencher concealed
Chrome VTN.CN.KT8.CP
Gold Plated VTN.CN.KT8.GD



Valenteena™ adjustable height shower kit exposed
Chrome VTN.FLX.EXP.CP
Gold Plated VTN.FLX.EXP.GD



Valenteena™ 5" drencher exposed
Chrome VTN.EXP.KT5.CP
Gold Plated VTN.EXP.KT5.GD



Valenteena™ 5" drencher concealed
Chrome VTN.CN.KT5.CP
Gold Plated VTN.CN.KT5.GD



Valenteena™ 8" drencher exposed
Chrome VTN.EXP.KT8.CP
Gold Plated VTN.EXP.KT8.GD



www.elisabathrooms.com

The Flyers Way, Westerham, Kent TN16 1DE, UK

Register your guarantee instantly at
www.elisabathrooms.com/service-and-support/register-your-guarantee

Speak to our Customer Service team on
01959 560003



The company reserves the right to alter, change or modify the product specifications without prior warning.

Q5683 Part No 706421 Issue 02 - Feb 22